

Key Features:

- Trade sizes 1/2" to 6"
- 10 or 20 foot lengths
- Socket on one end
- NEMA TC-2 and UL 651 Standards
- Rated for 90°C conductors
- Corrosion and rust proof
- Sunlight resistant (per UL 651)
- Non-conductive for your safety
- Lightweight - easy handling and installation
- Above ground and underground applications
- Solvent cement weld assembly

How to buy:

- Sold in full bundles
- Freight included
- **Call 945-212-7111**

Certifications:

- Approved for all government projects
- Approved for all DOT projects
- Buy America Act compliant
- Build America, Buy America compliant
- UL or ETL Certified
- Made in the USA



Part Number	Trade Size (in)	Length (ft)	Average O.D. (in)	Nom. I.D. (in)	Crate Quantity (ft)	Approx. lbs. per 100'	Crate weight (lbs.)
0508010	1/2	10	0.840	0.546	6,000	22	1320
0758010	3/4	10	1.050	0.742	4,400	30	1320
1008010	1	10	1.315	0.957	3,600	42	1512
1258010	1-1/4	10	1.660	1.278	3,300	60	1980
1508010	1-1/2	10	1.900	1.500	2,250	72	1620
2008010	2	10	2.375	1.939	1,400	98	1372
2508010	2-1/2	10	2.875	2.323	930	160	1488
3008010	3	10	3.500	2.900	880	213	1874
3508010	3-1/2	10	4.000	3.365	630	255	1607
4008010	4	10	4.500	3.826	570	309	1761
5008010	5	10	5.563	4.813	380	430	1634
6008010	6	10	6.625	5.760	260	589	1531
0508020	1/2	20	0.840	0.546	12,000	22	2640
0758020	3/4	20	1.050	0.742	8,800	30	2640
1008020	1	20	1.315	0.957	7,200	42	3024
1258020	1-1/4	20	1.660	1.278	6,600	60	3960
1508020	1-1/2	20	1.900	1.500	4,500	72	3240
2008020	2	20	2.375	1.939	2,800	98	2744
2508020	2-1/2	20	2.875	2.323	1,860	160	2976
3008020	3	20	3.500	2.900	1,760	213	3749
3508020	3-1/2	20	4.000	3.365	1,260	255	3213
4008020	4	20	4.500	3.826	1,140	309	3523
5008020	5	20	5.563	4.813	760	430	3268
6008020	6	20	6.625	5.760	520	589	3063